

**KT-1226 PORTABLE GASOLINE ENGINE GENERATOR**

**1KV**
**MODEL: (GE1200)1KV (ECO)**  
**RATE : 65000/-**

Product Specification  
 Wattage : 1 KW  
 Fuel Type : Gasoline  
 Power Source Fuel Powered  
 Recommended Uses For Product Residential  
 Item Weight : 31 Kilograms  
 Voltage : 220 Volts  
 Special Feature Overload Protection  
 Included Components TOOL KIT ,  
 OWENERS MANUAL , 3 PIN TOP, OIL FUNNEL

**KT-1229 PORTABLE GASOLINE ENGINE GENERATOR**

**5KV**
**MODEL: (AF-6500)5KV**  
**RATE : 99500/-**

Product Specification  
 Power (kVA) : 5 kVA  
 Model Number : AF-6500  
 Phase Single Phase  
 Output Power (kVA) : 5.5 kva  
 Fuel Consumption (at 100% Load) 1 ltr

**KT-1227 PORTABLE GASOLINE ENGINE GENERATOR**
**MODEL: (GE3000P)3KV (ECO)**  
**RATE : 69000/-**

**3KV**

Product Specification  
 Wattage : 3 KW  
 Power Source Fuel Powered  
 Recommended Uses For Product Residential  
 Item Weight : 48 Kilograms  
 Voltage : 220 Volts  
 Special Feature Overload Protection  
 Included Components 3 PIN TOP ,  
 OIL FUNNEL, BATTERY WITH CLAMPS,  
 KEY SET, TOOL KIT, OWNER MANUAL  
 Product Dimensions: 63L x 50W x 60H Centimeters

**KT-1230 PORTABLE GASOLINE ENGINE GENERATOR**
**MODEL: (AF-7500)7KV**  
**RATE : 119000/-**

**7KV**

Product Specification  
 Power: Single-cylinder/4-stroke/  
 Air-Cooled 190F  
 Displacement : 420cc  
 Rated Output Voltage : 230v~  
 Rated Frequency : 50Hz  
 Output Rating : 6500W  
 Continuous Working Time : 8h  
 Net Weight : 76kg  
 Features  
 1. Single-phase electricity output;  
 2. Manual start.

**KT-1228 PORTABLE GASOLINE ENGINE GENERATOR**
**MODEL: (AF3600)3KV**  
**RATE : 75000/-**

**3KV**

Product Specification  
 Wattage : 3 KW  
 Power Source Fuel Powered  
 Recommended Uses For Product Residential  
 Item Weight : 48 Kilograms  
 Voltage : 220 Volts  
 Special Feature Overload Protection  
 Included Components 3 PIN TOP ,  
 OIL FUNNEL, BATTERY WITH CLAMPS,  
 KEYSSET, TOOL KIT, OWNER MANUAL  
 Product Dimensions  
 63L x 50W x 60H Centimeters

**KT-1231 PORTABLE GASOLINE ENGINE GENERATOR**
**MODEL: (AF9500E) 7.5KV**  
**RATE : 165000/-**

**7.5KV**

Product Specification  
 Model : AF9500E  
 Power: Single-cylinder/4-stroke/  
 Air-Cooled 192F  
 Displacement: 438cc  
 Rated Output Voltage: 230v~  
 Rated Frequency: 50Hz  
 Output Rating: 7500W  
 Continuous Working Time: 7h  
 Net Weight: 90kg approx  
 Features  
 1. Single-phase electricity output;  
 2. Electronic start.  
 Accessories & Package  
 Engine Oil, Oil Funnel, Plug (2pcs),  
 Tool Kit (Screwdriver, Wrench,  
 Spark Plug Socket Wrench),  
 Carton Packing

www.kittytools.com AN ISO 9001: 2015 CO. www.kittytools.com

**KT-1232 PORTABLE GASOLINE ENGINE GENERATOR**


**Product Specification**  
 Wattage 3 KW  
 Power Source Fuel Powered  
 Recommended Uses  
 For Product Residential  
 Item Weight 44 Kilograms  
 Voltage 230 Volts  
 Special Feature Overload Protection  
 Included Components 3 PIN TOP ,  
 OIL FUNNEL, BATTERY WITH CLAMPS,  
 KEYSET, TOOL KIT, OWNER MANUAL  
 Product Dimensions  
 63L x 50W x 60H Centimeters

**MODEL: (SZ3000WE) 3KV**  
**RATE: 95000/-**

**3KV**

**KT-1233 PORTABLE GASOLINE ENGINE GENERATOR**


**Product Specification**  
 Power (kVA) 5 kVA Model Number : 6500  
 Phase : Single Phase Output Power (kVA) 5.5 kva  
 Fuel Consumption (at 100% Load) 1 ltr

**MODEL: (SZ-5500) 5KV**  
**RATE: 109500/-**

**5KV**

**KT-1234 PORTABLE GASOLINE ENGINE GENERATOR**


**Product Specification**  
 Power: Single-cylinder/4-stroke/Air-Cooled 190F  
 Displacement: 420cc  
 Rated Output Voltage: 230v~  
 Rated Frequency: 50Hz  
 Output Rating: 6500W  
 Continuous Working Time: 8h  
 Net Weight: 76kg  
 Features  
 1. Single-phase electricity output;  
 2. Manual start.

**MODEL: 7KV**  
**RATE: 129000/-**

**7KV**

**KT-1235 PORTABLE GASOLINE SILENT GENERATOR**


THE OUTPUT VOLTAGE: 230V~  
 RATED FREQUENCY : 50Hz  
 RATED OUTPUT POWER : 1.8KW  
 MAXIMUM OUTPUT POWER: 2.0KW  
 USB OUTPUT : 5V/1A,5V/2A  
 RATED SPEED : 4800RPM  
 DISPLACEMENT : 79.8CC  
 FUEL TYPE : GASOLINE  
 FUEL TANK CAPACITY : 4L  
 LUBRICANT TANK CAPACITY : 0.35L  
 START : HAND/ELECTRIC START  
 DIMENSIONS (LxWxH): 48\*28.6\*46CM  
 NET WEIGHT : 18KG

**OUTPUT : 1.8KV**  
**MODEL: TGGI-1800 TGGI-1800E (SELF START)**  
**RATE : 99000/- 105000/-**

**1.8KV**

**KT-1236 PORTABLE GASOLINE SILENT GENERATOR**


THE OUTPUT VOLTAGE: 230~  
 RATED FREQUENCY : 50Hz  
 RATED OUTPUT POWER : 2.2KW  
 MAXIMUM OUTPUT POWER: 2.4KW  
 USB OUTPUT : 5V/1A,5V/2A  
 RATED SPEED : 4800RPM  
 DISPLACEMENT : 97.7CC  
 FUEL TYPE : GASOLINE  
 FUEL TANK CAPACITY : 4.0L  
 LUBRICANT TANK CAPACITY : 0.35L  
 CONTINUOUS RUNNING TIME: 5H  
 START METHOD :  
 HAND START/ELECTRIC START  
 DIMENSIONS (LxWxH): 48\*28.5\*46CM  
 NET WEIGHT : 19.5KG

**MODEL: TGGI-2200 TGGI-2200E (SELF START)**  
**RATE : 110000/- 115000/-**

**2.2KV**

**KT-1237 PORTABLE GASOLINE SILENT GENERATOR**


THE OUTPUT VOLTAGE: 230V~  
 RATED FREQUENCY : 50Hz  
 RATED OUTPUT POWER : 3.5KW  
 MAX. OUTPUT POWER: 3.7KW  
 USB OUTPUT : 5V/1A,5V/2A  
 RATED SPEED : 3600RPM  
 DISPLACEMENT : 223CC  
 FUEL TYPE : GASOLINE  
 FUEL TANK CAPACITY : 12.5L  
 LUBRICANT TANK CAPACITY: 0.6L  
 CONTINUOUS RUNNING TIME: 5H  
 START METHOD :  
 HAND START/ELECTRIC START  
 DIMENSIONS (LxWxH): 63\*47\*54CM  
 NET WEIGHT : 40KG

**MODEL: TGGI-3500 TGGI-3500E (SELF START)**  
**RATE : 159000/- 164000/-**

**3.5KV**

www.kittytools.com AN ISO 9001: 2015 CO.



**KT-1238 LAWN MOVER MACHINE (ELECTRIC)**


**SPECIFICATION:**  
 POWER RATING : 1400W  
 SOUND PRESSURE LEVEL: 83DB  
 CUTTING HEIGHT : 20-55MM  
 CUTTING WIDTH : (18") 470MM  
 VIBRATION LEVEL : 2.5M/S2  
 WEIGHT : 11.6 KG.  
 CUTTING WIDTH : 370MM  
 HOLE DIA METRE : 8MM

**MODEL: ELECTRIC**  
**RATE : 23900/-**

**KT-1239 CORDLESS LAWN MOVER MACHINE**


**SPECIFICATION:**  
 POWER RATING :1400W  
 SOUND PRESSURE LEVEL: 83DB  
 CUTTING HEIGHT : 20-55MM  
 CUTTING WIDTH : (18") 470MM  
 VIBRATION LEVEL : 2.5M/S2  
 WEIGHT : 11.6 KG.  
 CUTTING WIDTH : 370MM  
 HOLE DIA METRE : 8MM

**MODEL: CORDLESS**  
**RATE : 159500/-**

**KT-1240 GASOLINE LAWN MOVER MACHINE**


**PRODUCT SPECIFICATION**  
 DRIVE TYPE : HAND PUSH  
 ENGINE TYPE : IP65F 4-STROCK AIR COOL  
 MAXI. POWER : 4.0HP  
 DISPLACEMENT : 139CC  
 RATED POWER : 1.85KW/2800RPM  
 CUTTING WIDTH : 460MM (18")  
 CUTTING HEIGHTS : 25-75MM/5 POSITION  
 HEIGHT ADJUSTMENT : CENTRAL ADJUSTMENT  
 CATCHER CAPACITY : 50L  
 WHEELS SIZE : 7"/8"  
 CATCHER MATERIAL : NYLON  
 DECK MATERIAL : STEEL  
 NOISE LEVEL : 96DB(A)

**MODEL: GASOLINE**  
**RATE : 199000/-**

**KT-1241 GASOLINE POWER SPRAYER**

**PRODUCT SPECIFICATION**  
 MODEL : AGS900  
 ENGINE TYPE : 4-STROCK SINGLE CYLINDER  
 DISPLACEMENT : 31CC  
 POWER OUTPUT : 1.0KW/1.3HP/7000RPM  
 MAX. ENGINE SPEED : 7500RPM  
 CARBURETOR TYPE : DIAPHRAGM  
 AIR FILTER (PAPER/PLASTIC FOAM) :FOAM  
 FUEL TANK CAPACITY RATIO : 25:1(GASOLINE 25:TWO-CYCLE OIL 1)  
 CHEMIST TANK (L) : 25L  
 CHEMIST TANK CAPACITY (ONLY LIQUID/LIQUID+POWER) : LIQUID  
 MAX AIR FLOWER(M3/H) : 1100M3/H  
 SPRAYER HORIZONTAL RANGE (M) : 15M  
 PLUNGER DIA : 18MM  
 PRESSURE : 15KG-25KG/CM2  
 OUTPUT : 6-8L/MIN  
 POWER : 139F/GX35  
 DRY WEIGHT(EXCL. CUTTING EQUIPMENT)) : 10.6KG (22LBS)  
 GROSS WEIGHT : 11KG(24.3LBS)  
 PACKING SIZE : 450\*330\*639MM



**MODEL: GASOLINE 4 STROKE**  
**RATE : 29900/-**


**KT-1242 MINI RICE MILL**

**Product Specification**

TYPE : 6N-40  
 CAPACITY : ABOVE 160KG/H  
 ELECTRIC POWER : 1.8-2.2KW  
 VOLTAGE : 220V  
 ROTOR SPEED (R/MIN) : 1600  
 ROTOR DIAMETER : 40  
 STRUCTURE STYLE OF : DISCONNECTED TYPE  
 APPLICATION : RICE , CORN, WHEAT, COFFEE, MILLET ETC.  
 FEATURES : HIGH SPEED, HIGH PRODUCTIVITY, ELECTRIC MOTOR, DIESEL  
 PATENT OF MILL BEARING, SHELLING RATE ABOVE 95%  
 PACKAGE : CARTON  
 NET WEIGHT : 30 KG.  
 GROSS WEIGHT : 32 KG.  
 ACCESSORIES : SS ROLLER AND SIEVE WITH HARDENING 20GP QUALITY : 300PCS(410X310X550MM)

**WITH 2.2 KW MOTOR**  
**RATE : 59900/-**

**KT-1243 PORTABLE GASOLINE SILENT GENERATOR**

**Product Specification**

TYPE : 6N-80/9FC-21  
 CAPACITY : ABOVE 220KG/H  
 ELECTRIC POWER : 1.8-2.2KW  
 VOLTAGE : 220V  
 ROTOR SPEED (R/MIN) : RICE MILL 1600/PULVERIZER 5500  
 STRUCTURE STYLE OF : DISCONNECTED TYPE  
 STRUCTURE STYLE OF : TOOTH-CLAW TYPE  
 APPLICATION : ANY GRAIN  
 FEATURES : HIGH SPEED, HIGH PRODUCTIVITY, ELECTRIC MOTOR, FLAT/SQUARE TOOTH 3PCS-40PCS, 0.8-5MM MESH  
 PACKAGE : CARTON  
 NET WEIGHT : 56.5 KG  
 GROSS WEIGHT : 58.5 KG  
 ACCESSORIES : 2 SET SIFTER, TRIANGLE BEST

**WITH 2.2 KW MOTOR**  
**RATE : 79900/-**

**KT-1244 GASOLINE MINI TILLER (WEEDER MACHINE)**

**2 Stroke 62 Cc High Performance**  
**4 Stroke 71 Cc High Performance**  
 3 HP Engine, 2 Stroke Single Cylinder,  
 Max Power: 2.2kw/6500 RPM  
 Tilling Depth : 5-12 cm,  
 Tilling Width : 40 cm,  
 Fuel Tank Capacity: 1.2L,  
 Fuel Mixture Ratio : Petrol Two-cycle Oil (30:1)  
 Displacement : 62Cc,  
 Starting System : Recoil Starter,  
 Carburetor : Diaphragm,  
 Fuel : Petrol

**MODEL: 2 STROKE 4 STROKE**  
**RATE : 53900/- 59900/-**  
**SPARE ATTACHMENT : 9900/-**


**KT-1245 POWER TILLER (CULTIVATOR) MACHINE**

**Product Specification**  
 ENGINE TYPE : OHV, 4 STROKE  
 DISPLACEMENT : 85/212CC  
 BOREXSTROKE(MM) : 68X54  
 GEAR BOX MATERIAL : ALUMINUM  
 +CAST IRON2FWD+1REW  
 ROTATE SPEED (RPM) : FWD. (1) 81,  
 FWD (2) 112, REV.61  
 MAX POWER : 5HP / 7.0HP/3600RPM  
 FUEL TYPE : GASOLINE

TILLING DEPTH : 175-350MM  
 TILLING WIDTH : 900MM  
 FUEL TANK CAPACITY : 3.6L  
 OIL TANK CAPACITY : 0.6 L  
 SHIFT POSITION : 2 FWD. + 1 REV.  
 BLADE TYPE : 3-4 BLADE (24 PCS BLADES)  
 TYRE TYPE : 3.5-8 WHEEL  
 G.W./N.W. : 100KG/95KGS.  
 MEANS : 88.5X52X65 CM  
 TRANSMISSION : GEAR



**SPARE ATTACHMENT**

**CAPCITY : 5 HP (85CC)**  
**MODEL: (4STROKE)**  
**RATE : 89500/-**  
**SPARE ATTACHMENT :**



**7.5 HP (210CC)**  
**(4STROKE)**  
**99500/-**  
**11900/-**

[www.kittytools.com](http://www.kittytools.com) AN ISO 9001: 2015 CO.